



AGS 221 GEL

ART. NO: 3625 | GRAFFITI REMOVER

AGS 221 GEL is a graffiti and paint remover. For use on exterior and interior surfaces. **AGS 221 GEL** is mainly used on smooth factory made/painted surfaces. Can also be used on porous substrates. **AGS 221 GEL** is readily biodegradable.

INSTRUCTIONS FOR USE

AGS 221 GEL is used for graffiti and paint removal from smooth factory made/painted surfaces, e.g trains, coaches & buses, cars and industrial buildings etc. Can also be used on porous substrates.

Graffiti-removal from smooth surfaces

Apply a thick layer of **AGS 221 GEL** with a brush. Cover all graffiti and wait 3-5 minutes. Agitate the whole area with a brush. When the graffiti has dissolved, jet off with medium-pressure and preferably warm water. If required, repeat the process.

Graffiti-removal from porous surfaces

Apply **AGS 221 GEL** with airless sprayer or brush. Agitate the whole area with a brush. Leave area to dissolve all graffiti approximately ½ - 4 hours. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 ltrs/minute, (4-5 gal/minute).

Note!

For metal surfaces do not use too much pressure, as the effect can be negative. Instead, wipe with a sponge or cloth and rinse with warm water.

Dosage

Use as concentrate.

Consumption

0,3 - 1,0 litre/m².

Technical data

- Viscous yellowish fluid. The colour may vary.
- Packaging: 5 litre plastic jerricans or 20 litre plastic buckets.
- Density: 1.05 kg/litre.
- Faint solvent odour.
- Contains 2-Butoxyethanol, Dimethyl succinate.

Storage

Store at room temperature in original closed container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Gloves. Safety glasses in case of splashes.

Marking: Warning



Causes skin irritation. Causes serious eye irritation

Not classified as dangerous goods in ADR or IMDG.
For more information, see [MSDS](#).