



BETO

ART NO: 1302 | RUST REMOVER

Dissolves and loosens rust on iron. Used as a pickling agent on metal surfaces prior to painting.

BETO is used in baths to restore old rusty tools to a usable condition. Biodegradable.

BETO dissolves and loosens effectively rust on iron and steel surfaces.

BETO is also excellent as a pickling agent prior to painting galvanized surfaces (surfaces with zinc coating) and also prior to painting on concrete floors.

BETO is used in baths to restore old rusty tools to a usable condition.

BETO can in some cases replace blasting.

BETO may after neutralization be released into the sewer.

Dosage

Depending on contamination

Use as concentrate or dilute with 1-8 parts of water.

Pickling of concrete floor

Dilute with 4 parts of water.

Consumption

Approx. 0,5-1 liter mixed product/m².

Technical data

- Transparent liquid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,26 kg/litre.
- Low odour.
- pH approx. 1
- Contains phosphoric acid.

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Wear suitable protective clothing, gloves and eye/face protection.

Marking: Danger



Causes severe skin burns and eye damage.

Classified as dangerous goods at road and sea transport.

UN 1805, PHOSPHORIC ACID SOLUTION

Class: 8 PG: III

For more information, see [MSDS](#).